



S.N.

SQU Product Code

Description

Qty.

UOM

Remarks

1

MDIDGFDGF0001

CAMERA

10

EA

دائرة المشتريات

80d LCD screen
 HD input and USB input
 3-inch LCD touch screen with a resolution
 of 1040 dots
 Canon 80D has a 24.0-megapixel CMOS
 sensor (22.5 x 15 mm).
 Imaging resolution of 6000 x 4000 pixels
 Canons DIGIC 6 Image Processor.
 Canon EF / EF-S Lens Mount.
 Last Date for Submission:06/06/2022
 warranty 1 year

REQUISITION FORM

Requisition Number:7023220008

2

MDIWKSPST0071

CONNECTORS

4

NOS

HDMI Adapter, HDMI Converter, VGA

3

MDIEQUGEQ0003

HEADSET W/MIC.

30

NOS

3.5mm stereo splitter cable allows to easily
 connect stereo headset Mic to a PC audio
 port and mic port at the same time.In-
 Headset Audio Control: Includes an analog
 volume control wheel and mic mute switch
 on the headset for quick and convenient
 adjustments. Designed for Comfort:
 Exceptionally comfortable memory foam
 ear cushions and padded leatherette
 headband helps to focus on gaming.3.5mm
 Connection: Compatible with PC, PS4,
 Nintendo Switch and mobile devices via
 audio jack.
 + Comes with Audio Y Splitter Cable from
 male to 2 female (mic & audio)

4

MDI(R)(R)0008

LAMINATING
MACHINE

1

EA

Thermal laminator can fit up to A3 paper
 size, compatible with 80 to 125 micron
 thickness
 practical electrical device; Easy-to-access

					<p>key on its user-friendly interface Ideal for use on cards, lists, photos, and more; Durable, durable and easy to use Entry width: 230mm / Max lamination thickness: 0.5mm Laminating speed: 25cm/min / Power consumption: 220W Plug type variants: US; European Union Package Contents: 1 x Thermal Laminating</p>
5	MDIEQUSLD0001	SCREEN (WALL MOUNT)	1	NOS	<p>Colors (green, blue and white) cloth holder Lumtape Heavy Duty Backdrop Stand Support Photography Backdrop with Carrying Bag for Photography and Video Shooting Adjustable Height and Width - 5.6*10 ft/2*3 cm</p>
6	MDISPAAUD0001	MICROPHONE	2	NOS	<p>RF Modulation: GFSK (Gauss frequency Shift Keying) Frequency band: 2.4GHz (2405-2478MHz) Frequency response: 35Hz-14KHz?3dB Signal/Noise: 76dB or more Distortion: 0.1% or less (320,1 KHz,65mW output)</p> <p>connector type 3.5 mm Jack number of batteries 1 lithiumion requires batteries. polar pattern Omnidirectional hardware platform PC, Camcorder, Tablet, Camera, Smartphone, Audio recorder</p>

7	MDIEQULig	LIGHTING SYSTEM	4	NOS	Tripod LED Video Light
8	MDIEQUKE10001	LIGHTS	4	NOS	Photography Lighting GSKAIWEN 180 LED Light Photography Studio LED Lighting Kit Adjustable Light with Light Stand Tripod Photographic Video Fill Light + Handheld LED Video Light