



S.N.	SQU Product Code	Description	Qty.	UOM	Remarks
1	EQUINSSFI0002	HOT PLATE STIRRER	10	NOS	<p>The bestseller in laboratories: Strong motor for a higher range of speeds, additional temperature control mode for faster heating of medium</p> <p>"Integrated temperature control</p> <p>"Incl. PT 1000 temperature sensor (PT 1000.60)</p> <p>"Exact temperature and speed setting via digital display, even when switched off</p> <p>"Set safety temperature limit displayed digitally</p> <p>Last Date for supply: 06/06/2022</p> <p>"Hot Top indicator >> hot surface warning to prevent burns!</p> <p>"Digital error code display</p> <p>"With adjustable safety circuit of heating plate temperature (50 - 360 ?C)</p> <p>"Safety magnetic stirrer with heating, suitable for unsupervised operation</p> <p>"Bushing according to DIN 12878 for connecting a contact thermometer, e.g. ETS-D5, enables precise temperature control</p> <p>"High level of safety thanks to improved heat control technology</p> <p>"Enclosed assembly (IP 42) guarantees long service life</p> <p>"Aluminium heating plate for optimum heat transfer</p> <p>"Improved magnetic adhesion</p> <p>"Automatic switch-off if the connected external temperature sensor is not immersed in the medium. Function selectable, timeout time adjustable (Error 5).</p> <p>Below Accessories should be supplied:</p> <p>"Temperature sensor, stainless steel</p> <p>"Round bottom flask carrier 100, 50, 25 ml without handle</p>

Procurement Department

REQUISITION FORM

Requisition Number:7026220058

2	EQUCMDPHR0003	ANALYTICAL BALANCE	10	NOS	Measuring range: 0-220 g Resolution: 0.1 mg Accuracy: ? 0.5 mg 5" Touchscreen Windshield Calibration: internal
3	EQUINSLAT0001	LATHE MACHINE	1	NOS	Specifications: Centre Height 210mm Swing over Bed 420mm Swing over Cross Slide 130mm Distance between Centres 500mm Width of Bed 139mm Spindle Bore 20mm Spindle Taper MT3 Number of Spindle Speeds 7 Range of Speeds - Lathe 160-1360rpm Range of Speeds - Mill 117-1300rpm Metric Threads steps 0.2-6mm in 22 steps Imperial Threads 4-120 t.p.i. in 38 steps Automatic Feeds 0.05-0.35 in 12 steps Tail Stock Taper MT3 Tail Stock Quill Travel 80mm Compound Slide Travel 80mm Cross Slide Travel 185mm Mill Head Spindle Taper MT3 Mill Head Quill Travel 110mm Distance between Spindle and Table 306mm Milling Table Size 300 x 150mm T Slot Size 12mm Drilling Capacity 25mm Motor power 0.66kW (0.5hp) Power Supply 240V Net Weight 155kg Dimensions 930 x 690 x 1090 -----

					<p>Features:</p> <ul style="list-style-type: none">"Powered cross feed"Separate motor for lathe and mill"Large milling table"Lead screw guard"20mm spindle bore"Heavy-duty cast-iron construction"Capacitor start motors for high torque starting <p>-----</p> <p>Standard Accessories:</p> <ul style="list-style-type: none">"125mm 3 jaw chuck"1-13mm drill chuck and arbor"steel centres"Manual and parts list"4-way tool post"Milling draw bar"Combined vice/compound table"Change gears"Lathe and drill chuck guards"10mm lathe tools <p>include the following condition:</p> <ul style="list-style-type: none">1- 2 years warranty2- 10 years after sale support
--	--	--	--	--	--