Sultan Qaboos University
Procurement Department
جامعة السلطان قابوس
دائرة المشتريات

REQUISITION FORM

Requisition Number:7023220008

Last Date for Submission:06/06/2022

S.N.	SQU Product Code	Description	Qty.	UOM	Remarks
1	MDIDGFDGF0001	CAMERA	10	EA	80d LCD screen HD input and USB input 3-inch LCD touch screen with a resolution of 1040 dots Canon 80D has a 24.0-megapixel CMOS sensor (22.5 x 15 mm). Imaging resolution of 6000 x 4000 pixels Canons DIGIC 6 Image Processor. Canon EF / EF-S . Lens Mount. waranty 1 year
2	MDIWKSPTS0071	CONNECTORS	4	NOS	HDMI Adapter, HDMI Converter, VGA
3	MDIEQUGEQ0003	HEADSET W/MIC.	30	NOS	3.5mm stereo splitter cable allows to easily connect stereo headset Mic to a PC audio port and mic port at the same time.In-Headset Audio Control: Includes an analog volume control wheel and mic mute switch on the headset for quick and convenient adjustments. Designed for Comfort: Exceptionally comfortable memory foam ear cushions and padded leatherette headband helps to focus on gaming.3.5mm Connection: Compatible with PC, PS4, Nintendo Switch and mobile devices via audio jack. + Comes with Audio Y Splitter Cable from male to 2 female (mic & audio)
4	MDI(R)(R)0008	LAMINATING MACHINE	1	EA	Thermal laminator can fit up to A3 paper size, compatible with 80 to 125 micron thickness practical electrical device; Easy-to-access

					key on its user-friendly interface Ideal for use on cards, lists, photos, and more; Durable, durable and easy to use Entry width: 230mm / Max lamination thickness: 0.5mm Laminating speed: 25cm/min / Power consumption: 220W Plug type variants: US; European Union Package Contents: 1 x Thermal Laminating
5	MDIEQUSLD0001	SCREEN (WALL MOUNT)	1	NOS	Colors (green, blue and white) cloth holder Lumtape Heavy Duty Backdrop Stand Support Photography Backdrop with Carrying Bag for Photography and Video Shooting Adjustable Height and Width - 5.6*10 ft/2*3 cm
6	MDISPAAUD0001	MICROPHONE	2	NOS	RF Modulation: GFSK (Gauss frequency Shift Keying) Frequency band: 2.4GHz (2405-2478MHz) Frequency response: 35Hz-14KHz?3dB Signal/Noise: 76dB or more Distortion: 0.1% or less (32O,1 KHz,65mW output) connector type 3.5 mm Jack number of batteries 1 lithiumion requires batteries. polar pattern Omnidirectional hardware platform PC, Camcorder, Tablet, Camera, Smartphone, Audio recorder

7	MDIEQULig	LIGHTING SYSTEM	4	NOS	Tripod LED Video Light
8	MDIEQUKE10001	LIGHTS	4	NOS	Photography Lighting GSKAIWEN 180 LED Light Photography Studio LED Lighting Kit Adjustable Light with Light Stand Tripod Photographic Video Fill Light + Handheld LED Video Light