



## Requisition Form

Requisition Number: 7022/26/0025

Last Date for Submission: 09/03/2026

S.N.	SQU Product Code	Description	Qty	UOM	Remarks
1	EQUHEACEN0001	CENTRIFUGE	1	Nos	<p>Centrifuge, refrigerated, 230 V/50-60 Hz</p> <p>Complete package for your rotary evaporator setup.</p> <p>Specifications:</p> <ul style="list-style-type: none"> <li>- Max. rcf 20913 x-g</li> <li>- Max. speed 14000 1/min</li> <li>- Speed 14,000 1/min</li> <li>- With cooling Yes</li> <li>- Min. temperature -9 °C</li> <li>- Max. temperature 40 °C</li> <li>- Temperature -9 ... 40 °C</li> <li>- Dimensions (WxDxH) 700 x 350 x 350 mm</li> <li>- Rated capacity 1650 W</li> </ul> <p>Rotor incl.Quick-Lock</p> <p>For vessels 6 x 15/50 ml, conical</p> <p>Type of lid Aerosol-tight</p> <p>Max. rcf 20133 x-g</p> <p>Max. speed 12100 1/min</p> <p>-</p>
2	EQUAGRAGC0023	ROTARY EVAPORATOR	1	Pieces	<p>Rotary evaporator specifications:</p> <ul style="list-style-type: none"> <li>- Type of cooling: vertical</li> <li>- Cooling surface: 1500 cm2</li> <li>- Motor principle: DC</li> <li>- Speed range: 20 - 300 rpm</li> <li>- Stroke: 150 mm</li> <li>- Heating temperature range: room temp. - 99 °C</li> <li>- Vacuum pump: VACSTAR lite</li> <li>- Pump rate max. (50/60Hz): 1.0 m3/h</li> <li>- Pump rate max. (50/60Hz): 16.7 l/min</li> <li>- Final pressure: 9 mbar</li> <li>- Permissible ambient temperature: 5 - 40 °C</li> <li>- Voltage: 100 - 240 V</li> <li>- Frequency: 50/60 Hz</li> </ul> <p>Scope of delivery:</p> <ul style="list-style-type: none"> <li>- RV 3 FLEX</li> <li>- RV 10.1 Glassware vertical</li> <li>- VC 10 lite</li> <li>- VACSTAR lite</li> <li>- VC 10.600 Stand pole</li> <li>- RC 2 lite</li> <li>- RV 10.5005 Set of hoses</li> <li>- PC 1.3 Cable</li> </ul> <p>-Including the following:</p> <ul style="list-style-type: none"> <li>--Evaporation flask (NS 29/32, 3.000 ml)</li> </ul> <p>The flask is made of high quality borosilicate glass, 3000 ml.</p> <ul style="list-style-type: none"> <li>--Receiving flask, coated (KS</li> </ul>

S.N.	SQU Product Code	Description	Qty	UOM	Remarks
					35/20, 3.000 ml) The flask is made of high quality borosilicate glass, coated, 3000 ml.
3	EQUANADIR0001	WATER DISTILLER A	1	Nos	Duo™ Dual Quality Type 2 and Type 1 Water System Specification: - FEED WATER Specification: - • PressureBar: 0.1 – 6 - • Conductivity S/cm: < 1400 - • Hardness as CaCO3 ppm: < 400 Free Chlorine ppm: < 2 - • pH Value: 4 - 10 Iron (Total Fe) ppm: < 0.1 - Product Water Quality: - Dispense Water Quality (@25 °C / 77 °F): 18.2 M-cm = 0.05 uS/cm - Dispense Flow Rate: 2 L/miny - Auto Volumetric Dispense (@15 °C): 0.1 - 25 L - DI Quality (@25 °C): 15 M/cm - DI Make Up Rate (@15 °C): 20 L/hr - Particles: < 0.22 / ml - Bacteria: < 0.01 CFU/ml - TOC: 5 ppb - Endotoxins: < 0.001 EU/mL - Rnase: < 1 pg/mL - Dnase: < 5 pg/mL - Protease: < 0.15 g/mL -Storage Tank - 30L Volume